

EASYFLOOR™


The Best Way to Install In-Floor Radiant Heating

- A breakthrough product that dramatically simplifies the installation of in-floor hydronic radiant heat.
- Eliminates messy, hard-to-handle cement topping and offers vastly improved installation and design flexibility.
- The most efficient radiant heating system at an affordable price.
- Patented, modular grids snap together to form tubing runs to fit any room configuration.
- Builders, plumbers, mechanical contractors and many do-it-yourself home owners can readily install the system.
- Significantly reduces noise transmission between floors.

4

PexAlPex Tubing


Install PexAlPex tubing according to the layout on your floor plan and walk tubing into place as shown. The EasyFloor grids form a unique symmetrical pattern that accommodates straight runs, s-curves, and 90° or 180° turns. EasyFloor allows for on-the-spot design changes and tube runs in small or congested areas.



5

Pressure Test Manifold Hook-up

Pressure test the system before installing backer board. Complete PexAlPex tubing installation and connect the tubing to the manifold system. Finished distribution panels and complete panel installation instructions are available from FloorHeat.



6

Backer Board (Thermal Mass)

Lay backer board over the completed assembly and cut as required to fit room dimensions. Secure backer board by screwing through EasyFloor grids to the sub-floor. Secure one row of backer board at a time and cut to fit at end of run as needed.

